

WOCA Oil Refresher



- VOC free
- Ensures maximum dirt resistance and water resistance from day one
- Enhances the natural color of the wood
- Gently cleans and maintains the floor
- Oils the wood floor with each application
- Leaves a protective matte oil film on the surface of the wood floor

Available in containers of 1.0 quart and 2.5 quarts and in the colors Natural and White. Consumption: 1600 to 2100 sf per quart.



WOCA Oil Refresher is used for regular cleaning and maintenance of oiled wood floors. WOCA Oil Refresher, natural is typically used for natural oiled and color oiled floors and WOCA Oil Refresher white for white oiled wood floors.

WOCA Oil Refresher combines efficient cleaning with re-oiling as additional oil penetrates into the wood forming a protective matte layer in the surface.

INSTRUCTIONS:

1. Shake the bottle well before use.
2. The floor must be clean and free from dust before treatment.
3. Mix WOCA Oil Refresher with lukewarm water:
 - For traditionally oiled floors: 1:20 (1 cup WOCA Oil Refresher into 5 quarts of water).
 - For UV-oiled and oil-waxed floors: 1:40 (1/2 cup WOCA Oil Refresher into 5 quarts of water).The mixture ratio can vary depending on wear and requirement.
4. Wet floor with a lightly wrung floor mop or cloth lengthwise on the floor. Immediately afterwards, dip mop or floor cloth into

mixture and wipe the floor with well wrung mop or floor cloth again lengthwise on the wood. Use two buckets - one with WOCA Oil Refresher mixed with water and one with clear rinsing water. It is recommended to clean an area of approx. 100sf at a time. By doing it this way, the floor is exposed to moisture for a short period.

5. Leave the floor to dry for approx. two hours before use.
 6. If a light shine is desired, polish the dry floor with a white pad.
- Note: Oiled wood floors can also be cleaned regularly with WOCA Natural Soap 'Natural' or 'White' and re-oiled with WOCA Maintenance Oil or WOCA Maintenance Paste at regular intervals in residential areas and more often in commercial areas. On surfaces exposed to extremely hard wear, spot treatment can be done.*

Drying time: 2 hours at 68°F.

Consumption: Approx. 1600-2100 sf /quart.

Storage: Store in a cool dry place out of direct sunlight and high temperature.